

THESE TOOLS ARE DESIGNED TO BE USED WITH A TRENT BOSCH SUPER TOOL HANDLE AND/OR A TRENT BOSCH STABILIZER. YOU CAN ALSO MAKE WOODEN HANDLES FOR YOUR TOOLS – BE SURE TO MAKE THEM LONG ENOUGH SO YOU CAN DEAL WITH THE TORQUE INVOLVED IN THE PROCESS.

STRAIGHT TOOL USE:

TO USE THE STRAIGHT TOOL SET YOUR TOOL REST SO THAT THE CUTTER IS ON ABOUT CENTER AND PROCEED TO HOLLOW OUT THE PIECE. THE STRAIGHT TOOL IS USED FOR THE MAJORITY OF THE HOLLOWING PROCESS. EVERYTHING THAT YOU CAN REACH WITH THE STRAIGHT TOOL USE THE STRAIGHT TOOL FOR.

BENT TOOL USE:

TO USE THE BENT TOOL SET YOUR TOOL REST SO THAT THE CUTTER IS ON ABOUT CENTER THEN MOVE THE TOOL REST BACK SO THAT THE TOOL REST IS BEHIND THE BENT PORTION OF THE TOOL. THIS ALLOWS BETTER CONTROL OF THE TOOL. THE BENT TOOL IS PRIMARILY USED FOR CUTTING AROUND THE SHOULDER OF A HOLLOW FORM WHERE THE STRAIGHT TOOL IS UNABLE TO REACH.

SHARPENING:

DO NOT SHARPEN YOUR CARBIDE TIPS. YOU CAN LOOSEN THE TORX SCREW WITH THE TORX WRENCH (INCLUDED) AND ROTATE THE CARBIDE TIP IN A CLOCKWISE DIRECTION ¼ TO 1/3 TURN. THIS CAN BE DONE 3-4 TIMES BEFORE REPLACING THE CARBIDE TIP UNTIL THE ENTIRE TIP IS NO LONGER CUTTING AS DESIRED. LIFE OF THE TIPS WILL VARY DEPENDING ON THE MATERIAL BEING CUT.

TIP REPLACEMENT:

THE CARBIDE TIPS CAN BE REPLACED WHEN THEY ARE WORN OUT. SIMPLY REMOVE THE CARBIDE TIP USING THE TORX WRENCH TO REMOVE THE TORX SCREW. REPLACE THE CARBIDE TIP MAKING SURE THE CUTTER TIP IS FACING UP. REPLACE THE SCREW AND TIGHTEN DOWN SNUGLY. CONTINUE TURNING. (EXTRA TIPS AND SCREWS CAN BE PURCHASED THROUGH TRENT BOSCH STUDIOS OR THE DISTRIBUTOR WHO SOLD YOU YOUR TOOL.)

THANKS FOR PURCHASING THESE TOOLS! FOR FURTHER INSTRUCTIONS ON USE I HAVE INSTRUCTIONAL VIDEOS AVAILABLE. CHECK OUT WWW.TRENTBOSCH.COM FOR OTHER INNOVATIVE TOOLS. ENJOY YOUR NEW TOOL!

HAPPY TURNING,

TRENT BOSCH



TRENT BOSCH STUDIOS INC.

10520 NORTH COUNTY ROAD 17 + FORT COLLINS CO 80524 + 970 218 6453

TRENT@TRENTBOSCH.COM + WWW.TRENTBOSCHTOOLS.COM