



TRENT BOSCH TOTAL ACCESS HOLLOWING TOOLS

STRAIGHT TOOL BENT TOOL EXTREME BENT TOOL

THESE TOOLS ARE DESIGNED TO BE USED WITH A TRENT BOSCH SUPER TOOL HANDLES AND/OR THE TRENT BOSCH STABILIZER. YOU CAN ALSO MAKE WOODEN HANDLES FOR YOUR TOOLS – BE SURE TO MAKE THEM LONG ENOUGH SO YOU CAN DEAL WITH THE TORQUE INVOLVED IN THE PROCESS.

STRAIGHT TOOL USE:

TO USE THE STRAIGHT TOOL SET YOUR TOOL REST SO THAT THE CUTTER IS ON ABOUT CENTER AND PROCEED TO HOLLOW OUT THE PIECE. THE STRAIGHT TOOL IS USED FOR THE MAJORITY OF THE HOLLOWING PROCESS. EVERYTHING THAT YOU CAN REACH WITH THE STRAIGHT TOOL USE THE STRAIGHT TOOL FOR.

BENT TOOL USE:

TO USE THE BENT TOOL SET YOUR TOOL REST SO THAT THE CUTTER IS ON ABOUT CENTER THEN MOVE THE TOOL REST BACK SO THAT THE TOOL REST IS BEHIND THE BENT PORTION OF THE TOOL. THIS ALLOWS BETTER CONTROL OF THE TOOL. THE BENT TOOL IS PRIMARILY USED FOR CUTTING AROUND THE SHOULDER OF A HOLLOW FORM WHERE THE STRAIGHT TOOL IS UNABLE TO REACH.

SHARPENING:

SHARPENING YOUR NEW TOOLS IS VERY EASY. REMOVE THE TOOL FROM THE TOOL HANDLE, IF POSSIBLE. TAKE THE TOOL TO A GRINDER AND GRIND LIGHTLY ON THE TIP TO JUST SHARPEN THE EDGE. WHEN SHARPENING IT IS IMPORTANT TO REMEMBER THAT ALL YOU HAVE TO DO IS REMOVE A VERY SMALL AMOUNT OF METAL TO CREATE A SHARP NEW EDGE. [LINK TO SHARPENING VIDEO](#)

TIP REPLACEMENT:

THE TIPS ARE DESIGNED TO BREAK OFF AS A SAFETY FEATURE, SHOULD YOU HIT A NAIL OR BE CUTTING TOO AGGRESSIVELY. USE THE SAME PROCEDURE FOR REPLACING THE TIP AS DISCUSSED BELOW.

TO REPLACE YOUR TIPS WHEN THEY ARE WORN OUT, SIMPLY TAKE A PROPANE PLUMBERS TORCH AND HEAT THE END OF YOUR TOOL UP. THE SUPER GLUE, HOLDING THE TIP IN, WILL HEAT UP AND EXPAND AND ACTUALLY PUSH THE OLD TIP OUT. ONCE THE OLD TIP IS OUT LET THE TOOL COOL, AND CLEAN OUT ANY EXCESS GLUE THAT IS LEFT IN THE TOOL. TO GLUE THE NEW TIP IN, USE MEDIUM VISCOSITY SUPER GLUE. FILL THE HOLE IN THE TOOL WITH THE GLUE. GENTLY PRESS THE NEW TIP IN. EXCESS GLUE WILL SQUEEZE OUT. MAKE SURE THE CUTTER TIP IS UP AND FACING THE RIGHT DIRECTION. WIPE ANY EXCESS GLUE OFF AND SET ASIDE FROM THE GLUE TO CURE FOR ABOUT TEN MINUTES. CONTINUE TURNING. (EXTRA TIPS CAN BE PURCHASED THROUGH TRENT BOSCH STUDIOS OR THE DISTRIBUTOR WHO SOLD YOU YOUR TOOL.)

THANKS FOR PURCHASING THESE TOOLS! FOR FURTHER INSTRUCTIONS ON USE I HAVE INSTRUCTIONAL VIDEOS AVAILABLE. CHECK OUT WWW.TRENTBOSCH.COM FOR OTHER INNOVATIVE TOOLS. ENJOY YOUR NEW TOOL!

HAPPY TURNING,

TRENT BOSCH



TRENT BOSCH STUDIOS INC.

10520 NORTH COUNTY ROAD 17 + FORT COLLINS CO 80524 + 970 218 6453
TRENTBOSCH@YAHOO.COM + WWW.TRENTBOSCHTOOLS.COM